

## GTH 125/15K

Heavy duty wheel, with Blickle Extrathane® polyurethane tread, with cast iron wheel center

EAN 4047526266196

ID 266197

Customs tariff number 87169090



### Tread:

- high-quality polyurethane elastomer Blickle Extrathane®, hardness 92 Shore A
- low rolling resistance
- high abrasion resistance
- high cut and tear propagation resistance
- color light brown, non-marking, non-staining
- excellent chemical connection with the wheel center

### Wheel center:

- rugged gray cast iron
- lacquered, color silver

### Other features:

- high chemical resistance to many aggressive substances
- operating temperature: -5 °F to +160 °F, temporarily up to +195 °F, reduced load capacity over +105 °F



### Technical data:

Wheel Ø (D)	☞	125 mm
Wheel width	⌞	40 mm
Load capacity at 4 km/h	⚖	550 kg
Load capacity (static)	⚖	1,375 kg
Bearing type	⊙	ball bearing
Axle bore Ø (d)		15 mm
Hub keyway (T1)	⌘	45 mm
Temperature resistance min		-20 °C
Temperature resistance max		70 °C
Tread and tire hardness		92 Shore A
Unit weight	⚖	1.4 kg
Non-marking		✓
Non-staining		✓
Antistatic	⚡	×
ProductDetail.TechnicalData.Esd		×
Electrically conductive	⚡	×
Corrosion-resistant		×
Heat-resistant	🔥	×
Tread hydrolysis-resistant		×
Suitable for autoclaves		×

### Tread and tire hardness

■ ■ ■ ■ ■ □ 92 Shore A

### Rolling resistance

■ ■ ■ ■ ■ □ very good

### Wear resistance

■ ■ ■ ■ ■ □ excellent

### Operating noise / floor surface preservation

■ ■ ■ ■ □ □ good

