

## BS-GTH 250K

**Heavy duty welded steel fixed caster, heavy duty wheel, with Blickle Extrathane® polyurethane tread, with cast iron wheel center**

**EAN** 4047526267339

**ID** 267336

**Customs tariff number** 87169090



**rig:** BS series

- particularly robust welded steel construction
- zinc-plated, yellow-passivated, Cr6-free

**Wheel:** GTH series

- tread: high-quality polyurethane elastomer Blickle Extrathane®, hardness 92 Shore A, color light brown, non-marking, non-staining
- wheel center: rugged gray cast iron
- with grease nipple, lacquered, color silver

**Other features:**

- high chemical resistance to many aggressive substances
- operating temperature: -5 °F to +160 °F, temporarily up to +195 °F, reduced load capacity over +105 °F



**Technical data:**

Wheel Ø (D)	☉	250 mm
Wheel width	⊥	60 mm
Load capacity at 4 km/h	⬆	1,500 kg
Load capacity (static)	⬆	3,750 kg
Bearing type	☉	ball bearing
Total height (H)	⌀	305 mm
Plate size	☐	175 x 140 mm
Bolt hole spacing	⌓	140 x 105 mm
Bolt hole Ø	⌀	14 mm
Temperature resistance min		-20 °C
Temperature resistance max		70 °C
Tread and tire hardness		92 Shore A
Unit weight	⚖	11.6 kg
Non-marking	✓	
Non-staining	✓	
Antistatic	⚡	×
Electrically conductive	⚡	×
Corrosion-resistant		×
Heat-resistant	🔥	×
Tread hydrolysis-resistant		×
Suitable for autoclaves		×
Suitable for machine washing		×

**Tread and tire hardness**

■ ■ ■ ■ ■ □ 92 Shore A

**Rolling resistance**


■ ■ ■ ■ ■ □ very good

**Wear resistance**

■ ■ ■ ■ ■ □ excellent

**Operating noise / floor surface preservation**

■ ■ ■ ■ □ □ good



## Product references



**Corresponding swivel caster LS-GTH 250K**



**Wheel used GTH 250/25K**