

## ALEV 161/15K-EL

Heavy duty wheel, with "Blickle EasyRoll" elastic solid rubber tires, with aluminum wheel center, electrically conductive

EAN 4047526365608

ID 365601

Customs tariff number 87169090



### tire:

- high-quality elastic solid rubber "Blickle EasyRoll" in smooth rolling quality, hardness 71 Shore A
- very good operational comfort
- very good floor preservation, low-noise operation
- low rolling resistance
- color black
- vulcanised onto the wheel center

### Wheel center:

- die-cast aluminium

### Other features:

- high chemical resistance to many aggressive substances, except oils
- operating temperature: -5 °F to +175 °F, temporarily up to +210 °F, reduced load capacity over +140 °F
- electrical conductivity (ohmic resistance)  $\leq 10^4 \Omega$



### Technical data:

Wheel Ø (D)	☉	160 mm
Wheel width	⌈⌋	40 mm
Load capacity at 4 km/h	⊞	300 kg
Load capacity at 6 km/h	⊞	240 kg
Load capacity at 10 km/h	⊞	150 kg
Load capacity (static)	⊞	750 kg
Bearing type	☉	ball bearing
Axle bore Ø (d)		15 mm
Hub keyway (T1)	⋈	60 mm
Temperature resistance min		-20 °C
Temperature resistance max		80 °C
Tread and tire hardness		71 Shore A
Unit weight	⊞	0.8 kg
Non-marking		×
Non-staining		×
Antistatic	⌚	×
ProductDetail.TechnicalData.Esd		×
Electrically conductive	⌚	✓
Corrosion-resistant		×
Heat-resistant	⊞	×
Tread hydrolysis-resistant		×
Suitable for autoclaves		×

### Tread and tire hardness

■ ■ ■ ■ ■ 71 Shore A

### Rolling resistance

■ ■ ■ ■ ■ very good

### Wear resistance

■ ■ ■ ■ ■ good

### Operating noise / floor surface preservation

■ ■ ■ ■ ■ very good

