

## BS-SPO 150G

### Heavy duty welded steel fixed caster, nylon heavy duty wheel

EAN 4047526048464

ID 48462

Customs tariff number 87169090


**rig:** BS series

- particularly robust welded steel construction
- zinc-plated, yellow-passivated, Cr6-free














**Wheel:** SPO series

- high-quality nylon 6, impact resistant, hardness 70 Shore D, extremely robust heavy-duty version, color natural white

**Other features:**

- high chemical resistance to many aggressive substances
- operating temperature: -25 °C to +80 °C, reduced load capacity over +35 °C



**Technical data:**

Wheel Ø (D)		150 mm
Wheel width		50 mm
Load capacity at 4 km/h		800 kg
Load capacity (static)		2,000 kg
Bearing type		plain bore
Total height (H)		200 mm
Plate size		140 x 110 mm
Bolt hole spacing		105 x 75–80 mm
Bolt hole Ø		11 mm
Temperature resistance min		-25 °C
Temperature resistance max		80 °C
Tread and tire hardness		70 Shore D
Unit weight		2.5 kg
Non-marking		✓
Non-staining		✓
Antistatic		✗
Electrically conductive		✗
Corrosion-resistant		✗
Heat-resistant		✗
Tread hydrolysis-resistant		✗
Suitable for autoclaves		✗
Suitable for machine washing		✗

**Tread and tire hardness**
 70 Shore D

**Rolling resistance**
 excellent

**Wear resistance**
 good

**Operating noise / floor surface preservation**
 satisfactory


## Product references



**Corresponding swivel caster LS-SPO 150G**



**Wheel used SPO 150/20G**