

## BEV 415x100/305-ZST

Elastic solid rubber press-on band, vulcanised on the steel-band

EAN 4047526581213

ID 581215

Customs tariff number 40129020

### Press-on band:

- high-quality elastic solid rubber in drive-quality, hardness 65 Shore A
- very good operational comfort
- low rolling resistance
- abrasion-resistant
- very good floor preservation, low-noise operation
- color black
- vulcanised on the steel-band
- for wheel center with outer diameter tolerance h11

### Other features:

- chemical resistance to many aggressive substances, except oils
- operating temperature: -20 °F to +175 °F, temporarily up to +210 °F, reduced load capacity over +140 °F

### Technical data:

Wheel Ø (D)	⌀	415 mm
Outer Ø (D)	⌀	415 mm
Internal Ø (d)	⌀	305 mm
Wheel width	⌈	100 mm
Load capacity at 4 km/h	⌈	1,330 kg
Load capacity at 6 km/h	⌈	1,115 kg
Load capacity at 10 km/h	⌈	915 kg
Load capacity at 16 km/h	⌈	835 kg
Load capacity (static)	⌈	3,325 kg
Temperature resistance min		-30 °C
Temperature resistance max		80 °C
Tread and tire hardness		65 Shore A
Unit weight	⌘	10.8 kg
Non-marking		×
Non-staining		×
Antistatic	⌚	×
ProductDetail.TechnicalData.Esd		×
Electrically conductive	⌚	×
Corrosion-resistant		×
Heat-resistant	⌚	×
Tread hydrolysis-resistant		✓
Suitable for autoclaves		×



### Tread and tire hardness

■ ■ ■ ■ ■ 65 Shore A

### Rolling resistance

■ ■ ■ ■ ■ very good

### Wear resistance

■ ■ ■ ■ ■ good

### Operating noise / floor surface preservation

■ ■ ■ ■ ■ very good

