

PATH 200/20G

Wheel with thermoplastic polyurethane tread, with nylon wheel center

EAN 4047526110833

ID 746879

Customs tariff number 87169090



Tread:

- high-quality thermoplastic polyurethane (TPU), hardness 94 Shore A
- low rolling and swivel resistance
- high abrasion resistance
- color dark gray, non-marking, non-staining
- chemically-bonded inseparable connection with the wheel center

Wheel center:

- high-quality nylon 6, impact resistant
- color silver gray

Other features:

- very high chemical resistance to many aggressive substances
- operating temperature: -15 °F to +160 °F, temporarily up to +195 °F, reduced load capacity over +95 °F

Technical data:

Wheel Ø (D)	☉	200 mm
Wheel width	⌈⌋	40 mm
Load capacity at 4 km/h	⚖	500 kg
Load capacity (static)	⚖	1,250 kg
Bearing type	☉	plain bore
Axle bore Ø (d)		20 mm
Hub keyway (T1)	⌈⌋	60 mm
Temperature resistance min		-25 °C
Temperature resistance max		70 °C
Tread and tire hardness		94 Shore A
Unit weight	⚖	0.7 kg
Non-marking		✓
Non-staining		✓
Antistatic	⚡	✗
ProductDetail.TechnicalData.Esd		✗
Electrically conductive	⚡	✗
Corrosion-resistant		✓
Heat-resistant	🔥	✗
Tread hydrolysis-resistant		✗
Suitable for autoclaves		✗



Tread and tire hardness

■ ■ ■ ■ ■ □ 94 Shore A

Rolling resistance

■ ■ ■ ■ ■ □ very good

Wear resistance

■ ■ ■ ■ ■ □ very good

Operating noise / floor surface preservation

■ ■ ■ ■ □ □ good

