

## LE-PO 200R-ST-FA

**Pressed steel swivel caster, with top plate fitting, with brake system 'stop-top', nylon wheel, with steel thread guard**

**EAN** 4047526013592

**ID** 749582

**Customs tariff number** 87169090



**rig:** LE series

- pressed steel, zinc-plated, blue-passivated, Cr6-free
- double ball bearing in the swivel head
- swivel head seal
- minimum swivel head play and smooth rolling characteristic and increased service life due to the special dynamic Blickle riveting process

**Wheel:** PO series

- high-quality nylon 6, impact resistant, hardness 70 Shore D, color natural white

**Other features:**

- high chemical resistance to many aggressive substances
- operating temperature: -25 °C to +80 °C, reduced load capacity over +35 °C

**Technical data:**

Wheel Ø (D)	☞	200 mm
Wheel width	⏏	50 mm
Load capacity at 4 km/h	⚖	300 kg
Load capacity (static)	⚖	750 kg
Bearing type	⦿	roller bearing
Total height (H)	⏏	235 mm
Plate size	⏏	140 x 110 mm
Bolt hole spacing	⏏	105 x 75–80 mm
Bolt hole Ø	⏏	11 mm
Offset (F)	⏏	54 mm
Temperature resistance min		-25 °C
Temperature resistance max		70 °C
Tread and tire hardness		70 Shore D
Unit weight	⚖	2.7 kg
Non-marking		✓
Non-staining		✓
Antistatic	⏏	✗
Electrically conductive	⏏	✗
Corrosion-resistant		✗
Heat-resistant	⏏	✗
Tread hydrolysis-resistant		✗
Suitable for autoclaves		✗
Suitable for machine washing		✗



**Tread and tire hardness**

■■■■■ 70 Shore D

**Rolling resistance**



■■■■■ excellent

**Wear resistance**

■■■■■ good

**Operating noise / floor surface preservation**

■■■■■ satisfactory



## Product references



**Corresponding rigid caster B-PO 200R-FA**



**Corresponding swivel caster LE-PO 200R-FA**



**Wheel used PO 200/20R**