

## B-VWPP 200R

Pressed steel fixed caster, medium duty design, with top plate fitting, wheel with "Blickle Soft" soft rubber tire, with synthetic rim

EAN 4047526078218

ID 754251

Customs tariff number 87169090



**rig:** B series

- pressed steel, zinc-plated, blue-passivated, Cr6-free

**Wheel:** VWPP series

- tire: soft rubber "Blickle Soft", hardness 50 Shore A, color black (wheel Ø 260 mm with additional hard rubber core)
- rim: high-quality polypropylene, impact resistant, color black

**Other features:**

- high chemical resistance to many aggressive substances, except oils
- operating temperature: -20 °C to +60 °C, reduced load capacity over +30 °C
- wheel Ø 260 mm with additional hard rubber core
- puncture-proof alternatives for pneumatic tires



### Technical data:

Wheel Ø (D)	☞	200 mm
Wheel width	⏏	50 mm
Load capacity at 4 km/h	⚖	100 kg
Load capacity (static)	⚖	250 kg
Bearing type	⦿	roller bearing
Profile	⏏	round profile
Total height (H)	⏏	235 mm
Plate size	⏏	140 x 110 mm
Bolt hole spacing	⏏	105 x 75–80 mm
Bolt hole Ø	⏏	11 mm
Temperature resistance min		-20 °C
Temperature resistance max		60 °C
Tread and tire hardness		50 Shore A
Unit weight	⚖	2.1 kg
Non-marking		×
Non-staining		×
Antistatic	⚡	×
Electrically conductive	⚡	×
Corrosion-resistant		×
Heat-resistant	🔥	×
Tread hydrolysis-resistant		×
Suitable for autoclaves		×
Suitable for machine washing		×

#### Tread and tire hardness

■ ■ ■ ■ ■ 50 Shore A

#### Rolling resistance

■ ■ ■ ■ ■ good

#### Wear resistance

■ ■ ■ ■ ■ satisfactory

#### Operating noise / floor surface preservation

■ ■ ■ ■ ■ excellent

