

DSPKGSP0 200K

Twin flanged wheel of compressed cast nylon

EAN 4047526112769

ID 754296

Customs tariff number 87169090



Wheel:

- high-quality cast nylon, impact resistant, hardness 80 Shore D
- V-shaped tread (for angular steel)
- very low rolling resistance
- high abrasion resistance
- color natural beige

Other features:

- high chemical resistance to many aggressive substances
- operating temperature: -20 °C to +80 °C, reduced load capacity over +35 °C
- consider the surface pressure on sensitive floors due to high point loads



Technical data:

Wheel Ø (D)	☉	200 mm
Wheel width	⏏	33 mm
Recess width (B)	☐	25 mm
Load capacity at 4 km/h	⚖	500 kg
Load capacity (static)	⚖	1,250 kg
Bearing type	☉	ball bearing
Axle bore Ø (d)		20 mm
Hub keyway (T1)	⌘	33 mm
Temperature resistance min		-20 °C
Temperature resistance max		80 °C
Tread and tire hardness		80 Shore D
Unit weight	⚖	1.2 kg
Non-marking		✓
Non-staining		✓
Antistatic	⚡	✗
ProductDetail.TechnicalData.Esd		✗
Electrically conductive	⚡	✗
Corrosion-resistant		✗
Heat-resistant	🔥	✗
Tread hydrolysis-resistant		✗
Suitable for autoclaves		✗

Tread and tire hardness

 80 Shore D

Rolling resistance

 excellent

Wear resistance

 very good

Operating noise / floor surface preservation

 satisfactory
