

LKRA-VPA 150G-11-FI-FA-ER14

Light duty swivel caster with bolt hole fitting, with synthetic expander, with brake system 'stop-fix', wheel with solid rubber tires, with synthetic rim, with steel thread guard

EAN 4047526136659

ID 848421

Customs tariff number 87169090



rig: LKRA series

- pressed steel, zinc-plated, blue-passivated, Cr6-free
- double ball bearing in the swivel head
- strong central kingpin
- minimum swivel head play and smooth rolling characteristic and increased service life due to the special dynamic Blickle riveting process

Wheel: VPA series

- tire: high-quality solid rubber, hardness 80 Shore A, color gray, non-marking, non-staining
- rim: high-quality nylon 6 or polypropylene in the electrically conductive version "-EL", impact resistant, color black

Other features:

- high chemical resistance to many aggressive substances, except oils
- operating temperature: -20 °C to +60 °C, reduced load capacity over +30 °C

Technical data:

Wheel Ø (D)	⌀	150 mm
Wheel width	⊥	30 mm
Load capacity at 3 km/h	⬆	110 kg
Load capacity (static)	⬆	275 kg
Bearing type	⊙	plain bore
Total height (H)	⊘	185 mm
Internal tube dimension	⦶	30–35 mm
Offset (F)	⦶	40 mm
Temperature resistance min		-20 °C
Temperature resistance max		60 °C
Tread and tire hardness		80 Shore A
Unit weight	⚖	1.2 kg
Non-marking		✓
Non-staining		✓
Antistatic	⚡	✗
Electrically conductive	⚡	✗
Corrosion-resistant		✗
Heat-resistant	🔥	✗
Tread hydrolysis-resistant		✗
Suitable for autoclaves		✗
Suitable for machine washing		✗



Tread and tire hardness

■ ■ ■ ■ □ □ 80 Shore A

Rolling resistance



■ ■ ■ ■ □ □ good

Wear resistance

■ □ □ □ □ sufficient

Operating noise / floor surface preservation

■ ■ ■ ■ □ very good



Product references



Corresponding swivel caster LKRA-VPA 150G-11-FA-ER14



Wheel used VPA 150/12G