

B-VWPP 160R-SG

Pressed steel fixed caster, medium duty design, with top plate fitting, wheel with "Blickle Soft" soft rubber tire, with synthetic rim, non-marking, gray

EAN 4047526158637

ID 849982

Customs tariff number 87169090



rig: B series

- pressed steel, zinc-plated, blue-passivated, Cr6-free

Wheel: VWPP series

- tire: soft rubber "Blickle Soft", hardness 50 Shore A, color gray, non-marking (wheel Ø 260 mm with additional hard rubber core)
- rim: high-quality polypropylene, impact resistant, color black

Other features:

- high chemical resistance to many aggressive substances, except oils
- operating temperature: -20 °C to +60 °C, reduced load capacity over +30 °C
- wheel Ø 260 mm with additional hard rubber core
- puncture-proof alternatives for pneumatic tires



Technical data:

Wheel Ø (D)	⌀	160 mm
Wheel width	⊥	40 mm
Load capacity at 4 km/h	⚖	70 kg
Load capacity (static)	⚖	175 kg
Bearing type	⦿	roller bearing
Profile		round profile
Total height (H)	⊗	195 mm
Plate size	⊞	140 x 110 mm
Bolt hole spacing	⊞	105 x 75–80 mm
Bolt hole Ø	⌀	11 mm
Temperature resistance min		-20 °C
Temperature resistance max		60 °C
Tread and tire hardness		50 Shore A
Unit weight	⚖	1.5 kg
Non-marking		✓
Non-staining		✓
Antistatic	⚡	✗
Electrically conductive	⚡	✗
Corrosion-resistant		✗
Heat-resistant	🔥	✗
Tread hydrolysis-resistant		✗
Suitable for autoclaves		✗
Suitable for machine washing		✗

Tread and tire hardness

■ ■ ■ ■ ■ 50 Shore A

Rolling resistance


■ ■ ■ ■ ■ good

Wear resistance

■ ■ ■ ■ ■ satisfactory

Operating noise / floor surface preservation

■ ■ ■ ■ ■ excellent



Product references



Corresponding swivel caster L-VWPP 160R-SG



Wheel used VWPP 160/20R-SG