

B-POEV 80KFD

Pressed steel fixed caster, medium duty design, with top plate fitting, heavy duty wheel, with "Blickle EasyRoll" elastic solid rubber tires, with nylon wheel center, with synthetic thread guard, large, with additional ball bearing seals

EAN 4047526164126

ID 850362

Customs tariff number 87169090



rig: B series

- pressed steel, zinc-plated, blue-passivated, Cr6-free




















Wheel: POEV series

- tire: high-quality elastic solid rubber "Blickle EasyRoll" in smooth rolling quality, hardness 65 Shore A, color black
- wheel center: high-quality nylon 6, impact resistant, color black

Other features:

- large thread guard, with additional, ball bearing seals
- high chemical resistance to many aggressive substances, except oils
- operating temperature: -5 °F to +175 °F, temporarily up to +210 °F, reduced load capacity over +95 °F

Technical data:

Wheel Ø (D)		80 mm
Wheel width		32 mm
Load capacity at 4 km/h		140 kg
Load capacity (static)		350 kg
Bearing type		ball bearing (C)
Total height (H)		102 mm
Plate size		100 x 85 mm
Bolt hole spacing		80 x 60 mm
Bolt hole Ø		9 mm
Temperature resistance min		-20 °C
Temperature resistance max		80 °C
Tread and tire hardness		65 Shore A
Unit weight		0.4 kg
Non-marking		×
Non-staining		×
Antistatic		×
Electrically conductive		×
Corrosion-resistant		×
Heat-resistant		×
Tread hydrolysis-resistant		×
Suitable for autoclaves		×
Suitable for machine washing		×



Tread and tire hardness

 65 Shore A

Rolling resistance


 very good

Wear resistance

 good

Operating noise / floor surface preservation

 very good



Product references



Corresponding swivel caster L-POEV 80KFD



Wheel used POEV 80/8KFD