

LK-POEV 125XR-1-ST-SB-FA

Pressed steel swivel caster, heavy duty design, with brake system 'stop-top', heavy duty wheel, with "Blickle EasyRoll" elastic solid rubber tires, with nylon wheel center, non-marking, blue, with steel thread guard

EAN 4047526173739

ID 851067

Customs tariff number 87169090



rig: LK series

- strong pressed steel, zinc-plated, blue-passivated, Cr6-free
- double ball bearing in the swivel head
- strong central kingpin (from wheel Ø 125x50 mm)
- swivel head seal
- minimum swivel head play and smooth rolling characteristic and increased service life due to the special dynamic Blickle riveting process

Wheel: POEV series

- tire: high-quality elastic solid rubber "Blickle EasyRoll" in smooth rolling quality, hardness 65 Shore A, color blue, non-marking
- wheel center: high-quality nylon 6, impact resistant, color black

Other features:

- high chemical resistance to many aggressive substances, except oils
- operating temperature: -15 °F to +175 °F, temporarily up to +210 °F, reduced load capacity over +95 °F

Technical data:

Wheel Ø (D)	☉	125 mm
Wheel width	⊥	37 mm
Load capacity at 4 km/h	⬆	250 kg
Load capacity (static)	⬆	625 kg
Bearing type	⊙	roller bearing
Total height (H)	⊘	155 mm
Plate size	⊠	100 x 85 mm
Bolt hole spacing	⊠	80 x 60 mm
Bolt hole Ø	⌀	9 mm
Offset (F)	⊘	48 mm
Temperature resistance min		-25 °C
Temperature resistance max		70 °C
Tread and tire hardness		65 Shore A
Unit weight	⚖	1.4 kg
Non-marking		✓
Non-staining		✓
Antistatic	⚡	✗
Electrically conductive	⚡	✗
Corrosion-resistant		✗
Heat-resistant	🔥	✗
Tread hydrolysis-resistant		✗
Suitable for autoclaves		✗



Tread and tire hardness

■ ■ ■ ■ ■ 65 Shore A

Rolling resistance



■ ■ ■ ■ ■ very good

Wear resistance

■ ■ ■ ■ ■ good

Operating noise / floor surface preservation

■ ■ ■ ■ ■ very good



Product references



Corresponding rigid caster BK-POEV 125XR-1-SB-FA



Corresponding swivel caster LK-POEV 125XR-1-SB-FA



Wheel used POEV 125/15XR-SB