

# BH-PO 127R-FA

Pressed steel fixed caster, heavy duty design, with top plate fitting, nylon wheel, with steel thread guard

EAN 4047526196646  
ID 852755  
Customs tariff number 87169090



- rig:** BH series
- pressed steel, zinc-plated, blue-passivated, Cr6-free
  - heavy fork and top plate

- Wheel:** PO series
- high-quality nylon 6, impact resistant, hardness 70 Shore D, color natural white

- Other features:**
- high chemical resistance to many aggressive substances
  - operating temperature: -25 °C to +80 °C, reduced load capacity over +35 °C

**Technical data:**

Wheel Ø (D)	☞	125 mm
Wheel width	⏏	50 mm
Load capacity at 4 km/h	⚖	400 kg
Load capacity (static)	⚖	1,000 kg
Bearing type	⦿	roller bearing
Total height (H)	⌵	170 mm
Plate size	📏	140 x 110 mm
Bolt hole spacing	📏	105 x 75–80 mm
Bolt hole Ø	🔩	11 mm
Temperature resistance min		-25 °C
Temperature resistance max		80 °C
Tread and tire hardness		70 Shore D
Unit weight	⚖	1.6 kg
Non-marking		✓
Non-staining		✓
Antistatic	🧼	✗
Electrically conductive	🧼	✗
Corrosion-resistant		✗
Heat-resistant	🔥	✗
Tread hydrolysis-resistant		✗
Suitable for autoclaves		✗
Suitable for machine washing		✗



**Tread and tire hardness**

■■■■■ 70 Shore D

**Rolling resistance**


■■■■■ excellent

**Wear resistance**

■■■■□ good

**Operating noise / floor surface preservation**

■■■■□ satisfactory



## ProductDatasheet.ProductReferences



**Corresponding swivel caster LK-PO 127R-FA**



**Wheel used PO 127/20R**