Product Data Sheet

LEX-POBS 160XKA-FI

Stainless steel swivel caster, with top plate fitting, with brake system 'stop-fix', heavy duty wheel, with Blickle Besthane® Soft polyurethane tread, with nylon wheel center, with synthetic thread guard, small

EAN 4047526346942 ID 901236 Customs tariff number 87169090 Made in Germany

rig: LEX series

- high-quality chromium-nickel steel (1.4301/AISI 304), stainless steel, vibrationground finishing
- all parts including axle material are corrosion-resistant
- double ball bearing in the swivel head
- swivel head seal
- minimum swivel head play and smooth rolling characteristic and increased service life due to the special dynamic Blickle riveting process

Wheel: POBS series

- tread: high-quality polyurethane elastomer Blickle Besthane[®] Soft, hardness 75 Shore A, color blue, non-marking, non-staining, very low rolling resistance, high dynamic load capacity, corrosion and hydrolysis-resistant
- wheel center: high-quality nylon 6, impact resistant, color black

Other features:

- · with synthetic thread guard, small
- corrosion and hydrolysis-resistant
- high chemical resistance to many aggressive substances
- operating temperature: -5 °F to +160 °F, temporarily up to +195 °F, reduced load capacity over +95 °F

Technical data:


Wheel Ø (D)	Q	160 mm
Wheel width	. 0.	50 mm
Load capacity at 4 km/h	පී	300 kg
Load capacity (static)	පී	750 kg
Bearing type	۲	ball bearing (CC)
Total height (H)	ġ	195 mm
Plate size		140 x 110 mm
Bolt hole spacing	Ľ:	105 x 75–80 mm
Bolt hole Ø	4	11 mm
Offset (F)	Ğ	48 mm
Temperature resistance min		-20 °C
Temperature resistance max		70 °C
Tread and tire hardness		75 Shore A
Unit weight	ð	2.2 kg
Non-marking		✓
Non-staining		✓
Antistatic	(4)	×
Electrically conductive	(4)	×
Corrosion-resistant		✓
Heat-resistant	ŀ	×


Blickle











Tread hydrolysis-resistant	 ✓
Suitable for autoclaves	×
Suitable for machine washing	×

Product references



Corresponding rigid caster BX-POBS 160XKA



Corresponding swivel caster LEX-POBS 160XKA

