

BEHS-POEV 160KA-14-SG

Pressed steel fixed caster, heavy duty design, with top plate fitting, heavy duty wheel, with "Blickle EasyRoll" elastic solid rubber tires, with nylon wheel center, non-marking, gray, with synthetic thread guard, small

EAN 4047526330064

ID 910017

Customs tariff number 87169090

rig: BEHS series

- particularly robust welded steel construction, zinc-plated, blue-passivated, Cr6-free














Wheel: POEV series

- tire: high-quality elastic solid rubber "Blickle EasyRoll" in smooth rolling quality, hardness 65 Shore A, color gray, non-marking
- wheel center: high-quality nylon 6, impact resistant, color black

Other features:

- with synthetic thread guard, small
- high chemical resistance to many aggressive substances, except oils
- operating temperature: -5 °F to +175 °F, temporarily up to +210 °F, reduced load capacity over +95 °F

Technical data:

Wheel Ø (D)		160 mm
Wheel width		50 mm
Load capacity at 4 km/h		400 kg
Load capacity (static)		1,000 kg
Bearing type		ball bearing (CC)
Total height (H)		199 mm
Plate size		114.3 x 101.6 mm
Bolt hole spacing		66,68 x 92,1 / 76,2 x 76,2 mm
Bolt hole Ø		11 mm
Temperature resistance min		-20 °C
Temperature resistance max		80 °C
Tread and tire hardness		65 Shore A
Unit weight		2.1 kg
Non-marking		✓
Non-staining		✓
Antistatic		✗
Electrically conductive		✗
Corrosion-resistant		✗
Heat-resistant		✗
Tread hydrolysis-resistant		✗
Suitable for autoclaves		✗
Suitable for machine washing		✗



Tread and tire hardness

 65 Shore A

Rolling resistance


 very good

Wear resistance

 good

Operating noise / floor surface preservation

 very good



Product references



Corresponding swivel caster LEH-POEV 160KA-14-SG



Wheel used POEV 160/12KA-SG