

B-POG 125KA-12

Pressed steel fixed caster, medium duty design, with top plate fitting, nylon wheel, with synthetic thread guard, small

EAN 4047526332082

ID 910133

Customs tariff number 87169090

rig: B series

- pressed steel, zinc-plated, blue-passivated, Cr6-free

Wheel: POG series

- high-quality nylon 6, hardness 70 Shore D, color gray

Other features:

- with synthetic thread guard, small
- high chemical resistance to many aggressive substances
- operating temperature: -20 °C to +80 °C, reduced load capacity over +35 °C



Technical data:

Wheel Ø (D)	🌀	125 mm
Wheel width	⏏	40 mm
Load capacity at 4 km/h	⚖	250 kg
Load capacity (static)	⚖	625 kg
Bearing type	🌀	ball bearing (C)
Total height (H)	📏	155 mm
Plate size	📏	92 x 63.5 mm
Bolt hole spacing	📏	44,5 x 71 - 78 mm
Bolt hole Ø	📏	7.9 mm
Temperature resistance min		-20 °C
Temperature resistance max		80 °C
Tread and tire hardness		70 Shore D
Unit weight	📏	0.6 kg
Non-marking	✓	
Non-staining	✓	
Antistatic	✗	
Electrically conductive	✗	
Corrosion-resistant	✗	
Heat-resistant	✗	
Tread hydrolysis-resistant	✗	
Suitable for autoclaves	✗	
Suitable for machine washing	✗	

Tread and tire hardness

70 Shore D

Rolling resistance


excellent

Wear resistance

good

Operating noise / floor surface preservation

satisfactory



Product references



Corresponding swivel caster L-POG 125KA-12



Wheel used POG 125/10KA