

LEH-POG 200K-14-FI

Pressed steel swivel caster, heavy duty design, with brake system 'stop-fix', nylon wheel

EAN 4047526333447

ID 910225

Customs tariff number 87169090



rig: LEH series

- strong pressed steel, zinc-plated, blue-passivated, Cr6-free
- double ball bearing in the swivel head
- swivel head seal
- minimum swivel head play and smooth rolling characteristic and increased service life due to the special dynamic Blickle riveting process
- particularly resistant to shocks and impact due to one specially-shaped, hardened bearing seats















Wheel: POG series

- high-quality nylon 6, hardness 70 Shore D, color gray

Other features:

- high chemical resistance to many aggressive substances
- operating temperature: -20 °C to +80 °C, reduced load capacity over +35 °C

Technical data:

Wheel Ø (D)		200 mm
Wheel width		50 mm
Load capacity at 4 km/h		570 kg
Load capacity (static)		1,420 kg
Bearing type		ball bearing
Total height (H)		241 mm
Plate size		114.3 x 101.6 mm
Bolt hole spacing		66,68 x 92,1 / 76,2 x 76,2 mm
Bolt hole Ø		11 mm
Offset (F)		51 mm
Temperature resistance min		-20 °C
Temperature resistance max		80 °C
Tread and tire hardness		70 Shore D
Unit weight		2.9 kg
Non-marking		✓
Non-staining		✓
Antistatic		✗
Electrically conductive		✗
Corrosion-resistant		✗
Heat-resistant		✗
Tread hydrolysis-resistant		✗
Suitable for autoclaves		✗
Suitable for machine washing		✗



Tread and tire hardness

 70 Shore D

Rolling resistance


 excellent

Wear resistance

 good

Operating noise / floor surface preservation

 satisfactory



Product references



Corresponding rigid caster BEHS-POG 200K-14



Corresponding swivel caster LEH-POG 200K-14



Wheel used POG 200/20K