

POEV 60/8KF

Heavy duty wheel, with "Blickle EasyRoll" elastic solid rubber tires, with nylon wheel center, with synthetic thread guard, large

EAN 4047526415945

ID 942345

Customs tariff number 83022000



tire:

- high-quality elastic solid rubber "Blickle EasyRoll" in smooth rolling quality, hardness 65 Shore A
- very good operational comfort
- very good floor preservation, low-noise operation
- low rolling resistance
- color black
- vulcanised onto the wheel center

Wheel center:

- high-quality nylon 6, impact resistant
- color black

Other features:

- with synthetic thread guard, large
- high chemical resistance to many aggressive substances, except oils
- operating temperature: -5 °F to +175 °F, temporarily up to +210 °F, reduced load capacity over +95 °F

Technical data:

Wheel Ø (D)	☉	60 mm
Wheel width	⊥	34 mm
Load capacity at 4 km/h	⚖	120 kg
Load capacity (static)	⚖	300 kg
Bearing type	⊙	ball bearing (CC)
Axle bore Ø (d)		8 mm
Hub keyway (T1)	⋈	36 mm
Temperature resistance min		-20 °C
Temperature resistance max		80 °C
Tread and tire hardness		65 Shore A
Unit weight	⚖	0.1 kg
Non-marking	✗	
Non-staining	✗	
Antistatic	⚡	✗
ProductDetail.TechnicalData.Esd	✗	
Electrically conductive	⚡	✗
Corrosion-resistant	✗	
Heat-resistant	🔥	✗
Tread hydrolysis-resistant	✗	
Suitable for autoclaves	✗	



Tread and tire hardness

■ ■ ■ ■ ■ 65 Shore A

Rolling resistance

■ ■ ■ ■ ■ very good

Wear resistance

■ ■ ■ ■ ■ good

Operating noise / floor surface preservation

■ ■ ■ ■ ■ very good

