

## B-VPP 180G-FA

**Pressed steel fixed caster, medium duty design, with top plate fitting, wheel with standard solid rubber tire, with synthetic rim, with steel thread guard**

**EAN** 4047526009786

**ID** 9787

**Customs tariff number** 87169090



**rig:** B series

- pressed steel, zinc-plated, blue-passivated, Cr6-free














**Wheel:** VPP series

- tire: standard solid rubber, hardness 80 Shore A, color black
- rim: high-quality polypropylene, impact resistant, color black

**Other features:**

- high chemical resistance to many aggressive substances, except oils
- operating temperature: -20 °C to +60 °C, reduced load capacity over +30 °C

### Technical data:

Wheel Ø (D)		180 mm
Wheel width		50 mm
Load capacity at 4 km/h		170 kg
Load capacity (static)		425 kg
Bearing type		plain bore
Total height (H)		215 mm
Plate size		140 x 110 mm
Bolt hole spacing		105 x 75–80 mm
Bolt hole Ø		11 mm
Temperature resistance min		-20 °C
Temperature resistance max		60 °C
Tread and tire hardness		80 Shore A
Unit weight		2 kg
Non-marking		×
Non-staining		×
Antistatic		×
Electrically conductive		×
Corrosion-resistant		×
Heat-resistant		×
Tread hydrolysis-resistant		×
Suitable for autoclaves		×
Suitable for machine washing		×



### Tread and tire hardness

 80 Shore A

### Rolling resistance


 satisfactory

### Wear resistance

 sufficient

### Operating noise / floor surface preservation

 very good



## Product references



**Corresponding swivel caster L-VPP 180G-FA**



**Wheel used VPP 180/20G**